



US009410602B2

(12) **United States Patent**  
**Dewitz**

(10) **Patent No.:** **US 9,410,602 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **TRANSMISSION-PRELOADING METHOD  
FOR MEASURING AND TESTING A  
TRANSMISSION, IN PARTICULAR A  
DOUBLE CLUTCH TRANSMISSION, WHICH  
HAS AT LEAST TWO SUB-TRANSMISSIONS**

(71) Applicant: **THYSSENKRUPP SYSTEM  
ENGINEERING GMBH**, Heilbronn  
(DE)

(72) Inventor: **Ingo Dewitz**, Hannover (DE)

(73) Assignee: **Thyssenkrupp System Engineering  
GmbH**, Heilbronn (DE)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 392 days.

(21) Appl. No.: **14/157,954**

(22) Filed: **Jan. 17, 2014**

(65) **Prior Publication Data**  
US 2014/0130625 A1 May 15, 2014

**Related U.S. Application Data**  
(63) Continuation of application No.  
PCT/EP2012/064238, filed on Jul. 19, 2012.

(30) **Foreign Application Priority Data**  
Jul. 20, 2011 (DE) ..... 10 2011 108 013

(51) **Int. Cl.**  
**G01M 13/02** (2006.01)  
**G01M 15/00** (2006.01)  
**F16H 3/08** (2006.01)  
**F16H 61/688** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F16H 3/08** (2013.01); **G01M 13/025**  
(2013.01); **G01M 13/028** (2013.01); **F16H**  
**61/688** (2013.01); **Y10T 74/19251** (2015.01)

(58) **Field of Classification Search**  
CPC ..... G01M 15/00; G01M 13/02  
USPC ..... 73/115.02  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,356,724 A 11/1982 Ayoub et al.  
5,537,865 A \* 7/1996 Shultz ..... G01M 13/025  
73/115.02

**FOREIGN PATENT DOCUMENTS**

DE 56 375 A1 1/1966  
DE 19537639 A1 4/1997  
DE 19934486 A1 1/2001  
DE 10 2004 037 982 A1 2/2006  
DE 10 2006 012 759 A1 9/2007

\* cited by examiner

*Primary Examiner* — Lisa Caputo


*Assistant Examiner* — Jamel Williams

(74) *Attorney, Agent, or Firm* — McNees Wallace & Nurick  
LLC


(57) **ABSTRACT**

A method for testing a transmission, in particular a double clutch transmission, is provided. A torque is introduced into the transmission by means of a drive unit that is external relative to the transmission, and the transmission is switched to an operating state in which an internal component of the transmission functions as a brake in order to simulate an output unit.

**15 Claims, 12 Drawing Sheets**



1a



1b